

*Amendments In the Claims*

Please amend Claims 1-5, 10, 20, 24-25, and 28 as follows:

1. (Currently Amended) A signal router comprising:  
a first switching matrix, wherein said first switching matrix has a first number of inputs and a second number of outputs;  
an error detector, coupled to one of said second number of outputs and  
selectably coupled to one of the first number of inputs, and  
configured to generate error information by virtue of being  
configured to detect errors in an information stream; and  
a controller, coupled to said first switching matrix and said error detector, wherein  
said controller is configured to  
select one of said first number of inputs from said first number of inputs,  
receive error information from said error detector, and  
configure said first switching matrix to couple said one of said first number of inputs to said one of said second number of outputs, and  
said first switching matrix is configured to receive said information stream  
at said one of said first number of inputs.
2. (Currently Amended) The signal router of claim 1, further comprising:  
a plurality of switching matrices, wherein  
said first switching matrix is one of said plurality of switching matrices,  
said first switching matrix is configured to identify said first switching matrix by virtue of said error information generated by said error detector.
3. (Currently Amended) The signal router of claim 2, further comprising:  
a plurality of error detectors, wherein

each one of said plurality of switching matrices is coupled to a  
corresponding one of said plurality of error detectors at one output  
of a plurality of outputs of said plurality of switching matrices,  
said first switching matrix is configured to identify at least one of said  
plurality of switching matrices by virtue of said error information  
generated by a corresponding one of said plurality of error  
detectors, and  
said at least one of said plurality of switching matrices experiences a  
failure detected by said corresponding one of said plurality of error  
detectors.

4. (Currently Amended) The signal router of claim 1, wherein said controller is  
further configured to reconfigure said first switching matrix in response to said error  
information.

5. (Currently Amended) The signal router of claim 1, wherein said controller  
further configures said first switching matrix to couple said one of said first number of  
inputs to another of said second number of outputs in addition to said one of said second  
number of outputs.

6. (Original) The signal router of claim 1, further comprising:  
a plurality of receivers, each one of said plurality of receivers coupled to a  
corresponding one of said first number of inputs and including a receiver  
error detector configured to detect errors in a received information stream;  
and  
a plurality of transmitters, each one of said plurality of transmitters coupled to a  
corresponding one of said second number of outputs and including a  
transmitter error detector configured to detect errors in an information  
stream to be transmitted, wherein said error detector further localizes a  
source of said errors by virtue of being configured to detect errors  
occurring after said receiver error detector of said each one of said

plurality of receivers and before said transmitter error detector of said each one of said plurality of transmitters.

7. (Original) The signal router of claim 6, wherein said each one of said plurality of receivers is an optical receiver and said each one of said plurality of transmitters is an optical transmitter.

8. (Previously Presented) The signal router of claim 1, further comprising:  
a clock and data recovery unit coupled between said one of said second number of outputs and said error detector; and  
a demultiplexer coupled between said clock and data recovery unit and said error detector.

9. (Previously Presented) The signal router of claim 8, wherein said clock and data recovery unit comprises a phase-locked loop.

10. (Currently Amended) The signal router of claim 1, wherein said information stream comprises a plurality of frames and said error detector comprises:  
an error checker, coupled to said first switching matrix and said controller,  
wherein  
said error checker is configured to generate error check information, and  
said error check information is included in said error information; and  
a framing circuit, coupled to said first switching matrix, said controller, and said error checker, and configured to  
detect a start-of-frame condition for each one of said plurality of frames,  
indicate said start-of-frame condition to said error checker,  
detect an end-of-frame condition for each one of said plurality of frames,  
indicate said end-of-frame condition to said error checker, and  
detect framing error, said framing error included in said error information.

11. (Original) The signal router of claim 10, wherein said framing error is an error in a set of errors that includes a loss-of-frame error, an out-of-frame error, and a loss-of-signal error.

12. (Original) The signal router of claim 10, said error detector further comprising:

an integrator, coupled between said error checker and said controller, and coupled between said framing circuit and said controller, wherein said integrator is configured to determine an error rate, said error rate is determined by counting said occurrence of said error during a period of time. and said error information comprises said error rate.

13. (Original) The signal router of claim 10, wherein:

said error checker and said framing circuit are coupled to an error counter, said error counter is configured to maintain an error count by virtue of being configured to count an occurrence of an error detected by at least one of said error checker and said framing circuit, said controller is configured to reset said error counter, periodically read an error count from said error counter, and calculate an error rate based on said error count, said error information comprising said error count.

14. (Original) The signal router of claim 13, wherein:

said error detector further comprises an error limit register and a comparator, said comparator is coupled to said error counter and said error limit register, said controller is further configured to load an error limit into said error limit register, and periodically read said error count from and reset said error counter in response to a signal generated by said error detector, said signal is generated by said comparator when said error count is equal to said error limit.

15. (Original) The signal router of claim 10, wherein:

said error checker and said framing circuit are coupled to an error counter,  
said error counter is configured to

maintain an error count by virtue of being configured to count an  
occurrence of an error detected by at least one of said error checker  
and said framing circuit, and

reset said error count upon said error count being read,  
said controller is configured to periodically read an error count from said error  
counter, and calculate an error rate based on said error count, said error  
information comprising said error count.

16. (Original) The signal router of claim 15, wherein:

said error detector further comprises an error limit register and a comparator,  
said comparator is coupled to said error counter and said error limit register,  
said controller is further configured to load an error limit into said error limit  
register, and periodically read said error count from said error counter in  
response to a signal generated by said error detector,  
said signal is generated by said comparator when said error count is equal to said  
error limit.

17. (Original) The signal router of claim 10, wherein said information stream is a  
SONET stream and each one of said plurality of frames is in a SONET frame format.

18. (Original) The signal router of claim 10, wherein said error checker is a parity  
checker.

19. (Previously Presented) The signal router of claim 10, wherein each one of said plurality of frames contains an error check entry, and said error checker generates said error check information by analyzing one of said plurality of frames and comparing a result of said analyzing to an error check entry of another of said plurality of frames.

20. (Currently Amended) An error detection method comprising:  
sending a first command to a controller, said controller coupled to control a switching matrix and to an error detector, said command causing said controller to configure said switching matrix to selectably couple one of a plurality of inputs to one of a plurality of outputs, said one of said plurality of inputs configured to receive an information stream and said one of said plurality of outputs coupled to said error detector, wherein said one of said plurality of outputs is less than all of said plurality of outputs;  
generating error information by detecting errors, if any, in said information stream using said error detector; and  
retrieving said error information from said error detector using said controller.

21. (Previously Presented) The method of claim 20, wherein said controller configures said switching matrix to couple said one of said plurality of inputs to another of said plurality of outputs in addition to said one of said plurality of outputs.

22. (Original) The method of claim 20, wherein said generating error information comprises:

clearing an error counter of said error detector;  
starting an error timer; and  
until said error timer reaches a terminal value, incrementing said error counter each time an error is detected by said error detector.

23. (Original) The method of claim 20, wherein said information stream comprises a plurality of frames and said detecting errors comprises:

- generating a framing error if a framing circuit of said error detector detects an error in framing in said information stream, wherein said framing circuit is coupled to and provides framing information to an error checker of said error detector;
- if no said error in framing is detected, generating a check error for each erroneous frame of said plurality of frames that is processed by said error detector, said error checker detecting an error in said erroneous frame.

24. (Currently Amended) The method of claim 23 ~~20~~, wherein each one of said plurality of frames is a SONET frame and said framing error is an error in a set of errors that includes a loss-of-frame error, an out-of-frame error, and a loss-of-signal error.

25. (Currently Amended) The method of claim 23 ~~20~~, wherein said error checker is a parity checker and said check error is a parity error.

26. (Original) The method of claim 25, wherein:

- said plurality of frames are received by said error detector in a sequence,
- said error checker generates parity information for a currently-processed frame of said plurality of frames, said currently-processed frame at a position in said sequence, and
- said error checker compares said parity information to a parity entry in another of said plurality of frames.

27. (Original) The method of claim 26, wherein

- each one of said plurality of frames is a SONET frame,
- said parity entry is a B1 byte of said SONET frame, and
- said another of said plurality of frames is at another position in said sequence, said another position in said sequence immediately subsequent to said position in said sequence.

28. (Currently Amended) A failure detection method comprising:  
 sending a command to a plurality of controllers, wherein  
     each one of said controllers is coupled to control a corresponding one of a  
         plurality of switching matrices,  
     said each one of said controllers is coupled to control a corresponding one  
         of a plurality of error detectors,  
     each one of said switching matrices is coupled to at least one other of said  
         switching matrices,  
     said command causes said controller to configure said corresponding one  
         of said switching matrices to selectably couple one of a plurality of  
         inputs of said corresponding one of said switching matrices to one  
         of a plurality of outputs of said corresponding one of said  
         switching matrices, and  
     said one of said inputs is configured to receive an information stream and  
     said one of said outputs is configured to output said information  
     stream by virtue of being coupled to said one of said inputs;  
 generating error information corresponding to said information stream by  
     detecting errors, if any, in said information stream using said one of the  
plurality of error detectors, wherein said one of the plurality of error  
detectors is coupled to said one of the plurality of outputs of said  
corresponding one of said switching matrices ~~said information stream~~; and  
 identifying failed ones of said switching matrices by retrieving said error  
 information corresponding to each one of said switching matrices.

29. (Original) The method of claim 28, wherein each one of a plurality of outputs  
 of a first plurality of said switching matrices are coupled to a corresponding one of a  
 plurality of inputs of a second plurality of said switching matrices.



30. (Original) The method of claim 28, wherein each one of said controllers configures said corresponding one of said switching matrices to couple said one of said inputs to another of said outputs in addition to said one of said outputs.

31. (Original) The method of claim 28, wherein said generating error information comprises:

clearing an error counter of said corresponding one of said error detectors;  
starting an error timer in said one of said controllers; and  
until said error timer in said one of said controllers reaches a terminal value,  
incrementing said error counter each time an error is detected by said  
corresponding one of said error detectors.

32. (Original) The method of claim 28, wherein said information stream comprises a plurality of frames and said detecting errors comprises:

generating a framing error if a framing circuit of said corresponding one of said  
error detectors detects an error in framing in said information stream,  
wherein said framing circuit is coupled to and provides framing  
information to an error checker of said corresponding one of said error  
detectors; and  
if no said error in framing is detected, generating a check error for each erroneous  
frame of said plurality of frames that is processed by said error detector,  
said error checker detecting an error in said erroneous frame.

33. (Previously Presented) A signal router comprising:

a switching matrix, wherein said switching matrix has a first number of inputs and  
a second number of outputs;  
an error detector, coupled to one of said second number of outputs and configured  
to generate error information by virtue of being configured to detect errors  
in an information stream; and  
a controller, coupled to said switching matrix and said error detector, wherein  
said controller is configured to

select one of said first number of inputs from said first number of inputs,  
 receive error information from said error detector, and  
 configure said switching matrix to couple said one of said first number of inputs to said one of said second number of outputs, and  
 said switching matrix is configured to receive said information stream at said one of said first number of inputs;  
 wherein said information stream comprises a plurality of frames and said error detector comprises:  
 an error checker, coupled to said switching matrix and said controller, wherein  
     said error checker is configured to generate error check information, and  
     said error check information is included in said error information;  
 a framing circuit, coupled to said switching matrix, said controller, and said error checker, and configured to  
     detect a start-of-frame condition for each one of said plurality of frames,  
     indicate said start-of-frame condition to said error checker,  
     detect an end-of-frame condition for each one of said plurality of frames,  
     indicate said end-of-frame condition to said error checker, and  
     detect framing error, said framing error included in said error information;  
 an integrator, coupled between said error checker and said controller, and coupled between said framing circuit and said controller, wherein  
     said integrator is configured to determine an error rate,  
     said error rate is determined by counting said occurrence of said error during a period of time. and  
 said error information comprises said error rate.

34. (Previously Presented) The signal router of claim 33, wherein:  
 said error checker and said framing circuit are coupled to an error counter,

said error counter is configured to maintain an error count by virtue of being configured to count an occurrence of an error detected by at least one of said error checker and said framing circuit,  
said controller is configured to reset said error counter, periodically read an error count from said error counter, and calculate an error rate based on said error count, said error information comprising said error count.

35. (Previously Presented) The signal router of claim 34, wherein:  
said error detector further comprises an error limit register and a comparator, said comparator is coupled to said error counter and said error limit register, said controller is further configured to load an error limit into said error limit register, and periodically read said error count from and reset said error counter in response to a signal generated by said error detector,  
said signal is generated by said comparator when said error count is equal to said error limit.

36. (Previously Presented) A signal router comprising:  
a switching matrix, wherein said switching matrix has a first number of inputs and a second number of outputs;  
an error detector, coupled to one of said second number of outputs and configured to generate error information by virtue of being configured to detect errors in an information stream; and  
a controller, coupled to said switching matrix and said error detector, wherein said controller is configured to  
select one of said first number of inputs from said first number of inputs,  
receive error information from said error detector, and  
configure said switching matrix to couple said one of said first number of inputs to said one of said second number of outputs, and

said switching matrix is configured to receive said information stream at said one of said first number of inputs;

wherein said information stream comprises a plurality of frames and said error detector comprises:

- an error checker, coupled to said switching matrix and said controller, wherein
  - said error checker is configured to generate error check information, and
  - said error check information is included in said error information; and
- a framing circuit, coupled to said switching matrix, said controller, and said error checker, and configured to
  - detect a start-of-frame condition for each one of said plurality of frames,
  - indicate said start-of-frame condition to said error checker,
  - detect an end-of-frame condition for each one of said plurality of frames,
  - indicate said end-of-frame condition to said error checker, and
  - detect framing error, said framing error included in said error information;

said error checker and said framing circuit are coupled to an error counter, said error counter is configured to

- maintain an error count by virtue of being configured to count an
  - occurrence of an error detected by at least one of said error checker and said framing circuit, and
- reset said error count upon said error count being read,

said controller is configured to periodically read an error count from said error counter, and calculate an error rate based on said error count, said error information comprising said error count.

37. (Previously Presented) The signal router of claim 36, wherein:

said error detector further comprises an error limit register and a comparator, said comparator is coupled to said error counter and said error limit register, said controller is further configured to load an error limit into said error limit register, and periodically read said error count from said error counter in response to a signal generated by said error detector,

said signal is generated by said comparator when said error count is equal to said error limit.

38. (Previously Presented) The signal router of claim 5, wherein said one of said second number of outputs provides the information stream to said error detector but is not a source of the information stream as an output of a switch node comprising the switching matrix; and said another of said second number of outputs is the source of the information stream as the output of the switch node.